

BRUSH SAW



Brush Saw: Special Application Kit must be installed on loader when operating the Brush Saw.

REQUIREMENTS

FEATURES & BENEFITS

- High-torque, low-speed motor increases efficiency while decreasing stalling.
- Manual 3-position boom angle.
- Left side discharge.
- Steel deflector shields protect operator and loader from flying debris.
- Cut slightly below ground level to minimise stumps.
- It has the ability to cut beyond mounting frame of saw when angled to the left.

Description: The Bobcat® brush saw attachment is a quick, convenient way to remove unwanted brush. It's ideal for cutting firebreaks, clearing pastures and grasslands, and cleaning road and utility line right-of-ways. The brush saw can cut slightly below ground level to minimise stumps often left by tree shears. The steel deflector shields protect the operator and loader from flying debris.

TECHNICAL SPECIFICATIONS

Description	Part Number	Disc Diameter (mm)	Disc Speed (rpm)	Number of Cutting Teeth	Flow Range (L/min)	Weight (kg)	Control Kit Required	Working Flow	First use installation time
Brush Saw, 75	7121030	750	400	16	56-87	267	No	Standard	None

COMPATIBILITY CHARTS

Description	Part Number	Compact Tracked Loaders						Skid Steer Loaders and All-Wheel Steer Loaders												
		MT55	T110	T590/H	T650/H	T770/H	T870/H	S70	S100	S450	S510	S530/H	S550/H	S570/H	S590/H	S630/H	S650/H	S770/H	S850/H	A770/H
Brush Saw, 75	7121030		X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X



Special application kit 7128395 must be installed on the machine. **

** To be ordered through Bobcat Parts